


MIKROELEKTRONIKA D.O.O, Batajnički drum 23, 11000 Belgrade, Serbia VAT: SR105917343 Registration No. 20490918

Phone: + 381 11 78 57 600 Fax: + 381 11 63 09 644 E-mail: office@mikroe.com

www.mikroe.com

Three-Axis Accelerometer Board



PID: MIKROE-254

The three-axis accelerometer board features a small, thin, low-power, complete 3-axis accelerometer ADXL330 with signal conditioned voltage outputs, all on a single monolithic IC.

Specifications

Туре	Motion
Applications	Three-Axis Accelerometer Board is a development tool for measuring static and dynamic acceleration
On-board modules	3-axis accelerometer ADXL330
Key Features	There is also a rail-to-rail Op Amp MCP6284 used for buffering. Analog voltage output
Interface	Analog
Compatibility	Breadboard (PROTO)
Input Voltage	5V

Downloads

Accel Board Dimensions

Three-Axis Accel Examples

Mikroe produces entire development toolchains for all major microcontroller architectures. Committed to excellency, we are dedicated to helping engineers bring the project development up to speed and achieve outstanding results.







MIKROELEKTRONIKA D.O.O, Batajnički drum 23, 11000 Belgrade, Serbia VAT: SR105917343 Registration No. 20490918 Phone: + 381 11 78 57 600 Fax: + 381 11 63 09 644 E-mail: office@mikroe.com www.mikroe.com

Accel Board User Manual

Mikroe produces entire development toolchains for all major microcontroller architectures. Committed to excellency, we are dedicated to helping engineers bring the project development up to speed and achieve outstanding results.







